


Two Piece Blade Connector_3-6Pin_3.0mm Pitch_Through Hole Series

Basic Specification

Rated Current : AC/DC 12V, 3A
Contact Resistance : 30mΩ MAX
Operational Temp. : -40℃~+85℃
Operational Durability : 2,000cycles
Floating Amount : ± 0.5mm



REFERENCE LAND PATTERN

Number of Contact	Rated Cyyrent	Dim.(mm)			Part Number	Compatible Product
		Pitch	A	B		
3	3.0A	3.0	9.0	6.0	TBCP-4725F-3-30-0000	TBR-6632F-3-30-0000
4	3.0A	3.0	12.0	9.0	TBCP-4725F-4-30-0000	TBR-6632F-4-30-0000
5	3.0A	3.0	15.0	12.0	TBCP-4725F-5-30-0000	TBR-6632F-5-30-0000
6	3.0A	3.0	18.0	15.0	TBCP-4725F-6-30-0000	TBR-6632F-6-30-0000

Electrical Characteristic

Rated Current : AC/DC 12V, 3A
Contact Resistance : 30mΩ MAX
Insulation Resistance : 100M Ω MIN
Dielectric Strength : 3mA (MAX) leakage

Mechanical Characteristics

Terminal pulling off force : Apply 2N static load on the terminal in axis direction for 1minute.

Insertion force : Measure the peak insertion force of initial condition.

Two Piece Blade Connector_3-6Pin_3.0mm Pitch_Through Hole Series**Other Characteristic**

Low Temp. Durability :	Store in temp $-40^{\circ}\text{C} \pm 3^{\circ}\text{C}$ for 96 hours, then leaves in the ambient temperature for 1 hour.
High Temp. Durability :	Store in temp $+85^{\circ}\text{C} \pm 2^{\circ}\text{C}$ for 96 hours, then leaves in the ambient temperature for 1 hour.
Humidity Durability :	Store in temp $+60^{\circ}\text{C} \pm 2^{\circ}\text{C}$ with humidity of 90 to 95% for 96 hours, then leave in the ambient temperature for 1 hour.
Temp. And Humidity Cycle Test :	Repeat 10 continuous temperature and humidity cycles that shown on Fig1, then leave in the ambient temperature for 1 hour.
Temp. Cycle Test :	Repeat 5 continuous temperature cycles that shown on Table1, then leave in the ambient temperature for 1 hour.
Anti-corrosion(Salt Water Spray) :	Spay saline water for 48hours. (Density : $5 \pm 1\%$ salt by weight, Temp : $35 \pm 2^{\circ}\text{C}$) After that, clean in lukewarm water and dry. Then leave in ambient temperature for 1 hour.
Vibration Test :	Connect each connector terminal in series and conducting 0.1A current. After that, apply the shock specified below. Amplitude : 1.5mm or 10G Sweeping cycle : 10~55~10Hz for 1min. Duration of test : 2hours for each of X, Y, Z axis.
Shock Test :	Connect each connector terminal in series and conducting 0.1A current. After that, apply the shock specified below. Acceleration rate : 50G(490m/s^2), half sine pulse Operation time : 11msec Duration : 3shocks in each X, Y, Z, axis both in negative and positive direction. (18shocks)
Soldering Heat Resistance :	Solder the each soldering terminal by soldering bit for the maximum of 3seconds at a temperature of 350degC.

Two Piece Blade Connector_3-6Pin_3.0mm Pitch_Through Hole Series

Table 1.Temperature Cycle

Step	Temperature(°C)	Time(minites)
1	-40 ± 3	30 - 35
2	5 - 35	10 - 15
3	85 ± 2	30 - 35
4	5 - 35	10 - 15

Fig 1. Temp. and Humidity Cycle



- The specifications shown in this catalogue are subject to change without notice.
- Storage conditions: 35days max in room temperature